

#AAD

Angelus Shoe Polish Co.
Santa Fe Springs, Ca. 90670

Product: Angelus No. 722 Duller
Date Prepared: 06/29/10

Section 1 Product Identification
Product Name: Angelus Duller for Acrylic Leather Paint
General or Generic ID: A proprietary Aqueous Silica Mixture

Hazard Rating: Health 1 Scale: 0 Minimal 1 Slight 2 Moderate 3 Serious 4 Severe
Fire 0
Reactivity 0

Emergency Phone Number 562-229-0521 Emergency Phone for Transportation only: 1-800-535-5053 INFOTRAC

Section 2 Composition/Information of Ingredients

Ingredient (s)	CAS Number	% (by volume)
Water	7732-18-5	>1%
Silica Gel	63231-67-4	<20%

Section 3 Hazards Identification Potential Health Effects

Eye: Can cause eye irritation. Symptoms include stinging, tearing, redness, and swelling of eyes.

Skin: May cause irritation of skin with prolonged use. No problem is expected with normal use.

Swallowing/Ingestion: May cause nausea. Vomiting may be induced at the discretion of a physician.

Inhalation: None, No adverse effect expected with normal use and adequate ventilation.

Symptoms of Exposure: None. No adverse effect expect with normal use..

Target Organ Effects: Not Determined

Developmental Info: Not Determined

Cancer Information: Based on the available information, this material cannot be classified with regard to carcinogenicity.

Primary Route of entry: Inhalation, Skin contact, Eye contact, Ingestion.

Other Health Effects: No Data

Section 4 First Aid Measures I

Eyes: Flush eyes gently with water for at least 15 minutes .Seek medical attention if irritation persists.

Skin: Wash affected skin areas thoroughly with soap and water. Consult physician if irritation persists.

Swallowing/Ingestion: If swallowed give 2 glasses of water. Consult a physician. Never give anything by mouth to an unconscious person. DO NOT INDUCE VOMITING unless directed by a Physician.

Inhalation: Move subject to fresh air. If symptoms persist consult a physician.

Page One Continued on next page

Angelus Shoe Polish

No. 722 Duller

Page 2

06/29/10

Section 5 Fire Fighting Measures

Flash Point: Noncombustible

Explosive Limit: Not Applicable

Autoignition Temp: Not Applicable

Hazardous products from Combustion: Not measured but toxic and irritating gases/fumes may be given off during burning.

Fire & Explosion Haz: Material may splatter above 212F/100C. Polymer film can burn.

Extinguishing Media: Use extinguishing media appropriate for surrounding fire.

Fire Fighting Instructions: Wear a self-contained breathing apparatus with a full face piece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protection equipment.

NFPA Rating: Health—1, Flammability---0, Reactivity--0

Section 6 Accidental Release Measures

Spill: Absorb liquid on vermiculite, floor absorbent, or other absorbent material and place in an approved container. Follow all regulations concerning disposal.

Section 7 Handling and Storage

Handling: Keep product from freezing..

Section 8 Exposure Controls / Personal Protection

Eye Protection: Under normal conditions eye protection is not necessary. It is however good practice to always wear protective glasses when using any product.

Skin Protection: Under normal conditions protections is not necessary. It is good practice to always avoid contact with skin.

Respiratory Protection: With normal ventilation respiratory protection is not necessary.

Exposure Guidelines: OSHA VPEL ACGIH TLV
Non Hazardous

Section 9 Physical and Chemical Properties

Boiling Point: 212F / 100C

Vapor Pressure: Not measured

Specific Vapor Density: AIR=1 <1 water

Page 2

Continued on next page

Angelus Shoe Polish

No. 722 Duller

Page 3

06/29/10

Section 9 continued Physical and Chemical Properties

Percent Volatiles: None

Volatile Organic Compounds (VOC) not established

Evaporation Rate: Slower than Ethyl Ether

Appearance: Clear /Milky liquid and various colors

State: Liquid

Physical Form: Homogeneous Solution

Color: White

Odor: minimal / odorless

pH N/A

Section 10 Stability and Reactivity

Hazardous Polymerization: Product will not undergo hazardous polymerization.

Hazardous Decomposition: By Fire: Carbon oxides, nitrogen oxides, Oxides of Silica

Chemical Stability: Stable

Incompatibility: There are no known materials which are incompatible with this product.

Section 11 Toxicological Information Acute Oral LD50:>4500 mg/kg (Rat) Repeated Dose Toxicity 6 months Oral: NOAEL: 10% (rat) Acute Inhalation LC50: >2 mg/l, 1 hrs. (rat) acute dermal: LD50: 200 mg/kg (rabbit)

Section 12 Ecological Information: Not readily biodegradable

Section 13 Disposal Consideration

Waste Management: Dispose of in accordance with all applicable local, state and federal regulations.

Section 14 Transport Information 49 CFR 172.101

Dot Description: Not Regulated

RQ (Reportable Qty) 49 CFR 172.101 Not applicable

Section 15

Regulatory Information

US Federal Regulations TSCS (Toxic Substances Control Act) Status

Cercla RQ-40CFR 302.4 (a)

RQ (lbs)

Cercla RQ-40CFR 302.4 (b)

Materials without a "listed" RQ may be reportable as an "unlisted hazardous substance. See CFR 302.5 (b)

Sara 302 Components- 40 CFR 355 Appendix A

NONE

Section 311/312 Hazard Class—40 CFR 370.2

Immediate () Delayed () Fire () Reactive () Sudden Release of Pressure ()

Sara 313 Components—40 CFR 372.65 Section 313 Component(s)

None

International Regulations inventory status: Not Determined

State and Local Regulations CALIFORNIA PROPOSITION 65

None

New Jersey RTK Label Information:

None

Pennsylvania RTK label information

None

Section 16

Other Information

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is, current, applicable, and suitable to their circumstances. No representation or warranties, either expressed or implied of fitness for a particular purpose or of any other nature to the product or to the information herein is made hereunder. Angelus shall in no event be responsible for any damages of whatsoever nature directly or indirectly resulting from the publication, or use of, or reliance upon the information contained herein.

#AAF - Matte

Angelus Shoe Polish Co.
Santa Fe Springs, Ca. 90670

Product: Angelus No. 620 Matte Acrylic Finisher
Date Prepared: 09/01/07

Section 1 Product Identification
Product Name: Angelus Matte Acrylic Finisher
General or Generic ID: A proprietary resin emulsion product

Hazard Rating: Health 1 Scale: 0 Minimal 1 Slight 2 Moderate 3 Serious 4 Severe
Fire 0
Reactivity 0

Emergency Phone Number 562-229-0521 Emergency Phone for Transportation only: 1-800-535-5053 INFOTRAC

Section 2 Composition/Information of Ingredients

Ingredient (s)	CAS Number	% (by volume)
Acrylic Polymer/wax emulsion blend		<9

Section 3 Hazards Identification Potential Health Effects

Eye: Can cause eye irritation. Symptoms include stinging, tearing, redness, and swelling of eyes.

Skin: May cause irritation of skin with prolonged use. No problem is expected with normal use.

Swallowing/Ingestion: May cause nausea. Vomiting may be induced at the discretion of a physician.

Inhalation: None, No adverse effect expected with normal use and adequate ventilation.

Symptoms of Exposure: None. No adverse effect expect with normal use..

Target Organ Effects: Not Determined

Developmental Info: Not Determined

Cancer Information: Based on the available information, this material cannot be classified with regard to carcinogenicity.

Primary Route of entry: Inhalation, Skin contact, Eye contact, Ingestion.

Other Health Effects: No Data

Section 4 First Aid Measures

Eyes: Flush eyes gently with water for at least 15 minutes .Seek medical attention if irritation persists.

Skin: Wash affected skin areas thoroughly with soap and water. Consult physician if irritation persists.

Swallowing/Ingestion: If swallowed give 2 glasses of water. Consult a physician. Never give anything by mouth to an unconscious person.

Inhalation: Move subject to fresh air. If symptoms persist consult a physician.

Angelus Shoe Polish No. 620 Matte Acrylic Finisher Page 21 09/01/07

Section 5 Fire Fighting Measures

Flash Point: Noncombustible

Explosive Limit: Not Applicable

Autoignition Temp: Not Applicable

Hazardous products
from Combustion: Not measured

Fire & Explosion Haz: Material may splatter above 212F/100C. Polymer film can burn.

Extinguishing Media: Use extinguishing media appropriate for surrounding fire.

Fire Fighting Instructions: Wear a self-contained breathing apparatus with a full face piece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protection equipment.

NFPA Rating: Health—1, Flammability---0, Reactivity--0

Section 6 Accidental Release Measures

Spill: Absorb liquid on vermiculite, floor absorbent, or other absorbent material and place in an approved container. Follow all regulations concerning disposal.

Section 7 Handling and Storage

Handling: Keep product from freezing..

Section 8 Exposure Controls / Personal Protection

Eye Protection: Under normal conditions eye protection is not necessary. It is however good practice to always wear protective glasses when using any product.

Skin Protection: Under normal conditions protections is not necessary. It is good practice to always avoid contact with skin.

Respiratory Protection: With normal ventilation respiratory protection is not necessary.

Exposure Guidelines: OSHA VPEL ACGIH TLV
Non Hazardous

Section 9 Physical and Chemical Properties

Boiling Point: 212F / 100C

Vapor Pressure Not measured

Specific Vapor Density: AIR=1 <1 water

 Section 9 continued Physical and Chemical Properties

Percent Volatiles: None

Volatile Organic Compounds (VOC) 400.0 g/l

Evaporation Rate: Slower than Ethyl Ether

Appearance: Clear /Milky liquid

State: Liquid

Physical Form: Homogeneous Solution

Color: No Data

Odor: minimal

pH N/A

 Section 10 Stability and Reactivity

Hazardous Polymerization: Product will not undergo hazardous polymerization.

Hazardous Decomposition: Thermal decomposition may yield acrylic monomers.

Chemical Stability: Stable

Incompatibility: There are no known materials which are incompatible with this product.

 Section 11 Toxicological Information
 No Data

 Section 12 Ecological Information: No Data

 Section 13 Disposal Consideration

Waste Management: Dispose of in accordance with all applicable local, state and federal regulations.

 Section 14 Transport Information 49 CFR 172.101

Dot Description: Not Regulated

RQ (Reportable Qty) 49 CFR 172.101 Not applicable

Section 15 Regulatory Information

US Federal Regulations TSCS (Toxic Substances Control Act) Status

Cercla RQ-40CFR 302.4 (a)

RQ (lbs)

Cercla RQ-40CFR 302.4 (b)

Materials without a "listed" RQ may be reportable as an "unlisted hazardous substance. See CFR 302.5 (b)

Sara 302 Components- 40 CFR 355 Appendix A

NONE

Section 311/312 Hazard Class—40 CFR 370.2

Immediate () Delayed () Fire () Reactive () Sudden Release of Pressure ()

Sara 313 Components—40 CFR 372.65 Section 313 Component(s)

None

International Regulations inventory status: Not Determined

State and Local Regulations CALIFORNIA PROPOSITION 65

None

New Jersey RTK Label Information:

None

Pennsylvania RTK label information

None

Section 16

Other Information

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is, current, applicable, and suitable to their circumstances. No representation or warranties, either expressed or implied of fitness for a particular purpose or of any other nature to the product or to the information herein is made hereunder. Angelus shall in no event be responsible for any damages of whatsoever nature directly or indirectly resulting from the publication, or use of, or reliance upon the information contained herein.

Last Page

#AAF - Satin

Angelus Shoe Polish Co.
Santa Fe Springs, Ca. 90670

Product: Angelus No. 605 Satin Acrylic Finisher
Date Prepared: 12/01/06

Section 1 Product Identification
Product Name: Angelus Satin Acrylic Finisher
General or Generic ID: A proprietary resin emulsion product

Hazard Rating: Health 1 Scale: 0 Minimal 1 Slight 2 Moderate 3 Serious 4 Severe
Fire 0
Reactivity 0

Emergency Phone Number 562-229-0521 Emergency Phone for Transportation only: 1-800-535-5053 INFOTRAC

Section 2 Composition/Information of Ingredients

Ingredient (s)	CAS Number	% (by volume)
Blend of Acrylic Polymers and Copolymers		<9

Section 3 Hazards Identification Potential Health Effects

Eye: Can cause eye irritation. Symptoms include stinging, tearing, redness, and swelling of eyes.

Skin: May cause irritation of skin with prolonged use. No problem is expected with normal use.

Swallowing/Ingestion: May cause nausea. Vomiting may be induced at the discretion of a physician.

Inhalation: None, No adverse effect expected with normal use and adequate ventilation.

Symptoms of Exposure: None. No adverse effect expect with normal use..

Target Organ Effects: Not Determined

Developmental Info: Not Determined

Cancer Information: Based on the available information, this material cannot be classified with regard to carcinogenicity.

Primary Route of entry: Inhalation, Skin contact, Eye contact, Ingestion.

Other Health Effects: No Data

Section 4 First Aid Measures

Eyes: Flush eyes gently with water for at least 15 minutes .Seek medical attention if irritation persists.

Skin: Wash affected skin areas thoroughly with soap and water. Consult physician if irritation persists.

Swallowing/Ingestion: If swallowed give 2 glasses of water. Consult a physician. Never give anything by mouth to an unconscious person.

Inhalation: Move subject to fresh air. If symptoms persist consult a physician.

Angelus Shoe Polish

No. 605 Satin Acrylic Finish

Page 2

12/01/06

Section 5	Fire Fighting Measures
Flash Point:	Noncombustible
Explosive Limit:	Not Applicable
Autoignition Temp:	Not Applicable
Hazardous products from Combustion:	Not measured
Fire & Explosion Haz:	Material may splatter above 212F/100C. Polymer film can burn.
Extinguishing Media:	Use extinguishing media appropriate for surrounding fire.
Fire Fighting Instructions:	Wear a self-contained breathing apparatus with a full face piece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protection equipment.
NFPA Rating:	Health—1, Flammability---0, Reactivity--0
Section 6	Accidental Release Measures
Spill:	Absorb liquid on vermiculite, floor absorbent, or other absorbent material and place in an approved container. Follow all regulations concerning disposal.
Section 7	Handling and Storage
Handling:	Keep product from freezing..
Section 8	Exposure Controls / Personal Protection
Eye Protection:	Under normal conditions eye protection is not necessary. It is however good practice to always wear protective glasses when using any product.
Skin Protection:	Under normal conditions protections is not necessary. It is good practice to always avoid contact with skin.
Respiratory Protection:	With normal ventilation respiratory protection is not necessary.
Exposure Guidelines: Non Hazardous	OSHA VPEL ACGIH TLV
Section 9	Physical and Chemical Properties
Boiling Point:	212F / 100C
Vapor Pressure	Not measured
Specific Vapor Density:	AIR=1 <1 water

 Section 9 continued Physical and Chemical Properties

Percent Volatiles: None

Volatile Organic Compounds (VOC) 400.0 g/l

Evaporation Rate: Slower than Ethyl Ether

Appearance: Clear /Milky liquid

State: Liquid

Physical Form: Homogeneous Solution

Color: No Data

Odor: minimal

pH N/A

 Section 10 Stability and Reactivity

Hazardous Polymerization: Product will not undergo hazardous polymerization.

Hazardous Decomposition: Thermal decomposition may yield acrylic monomers.

Chemical Stability: Stable

Incompatibility: There are no known materials which are incompatible with this product.

 Section 11 Toxicological Information
 No Data

 Section 12 Ecological Information: No Data

 Section 13 Disposal Consideration

Waste Management: Dispose of in accordance with all applicable local, state and federal regulations.

 Section 14 Transport Information 49 CFR 172.101

Dot Description: Not Regulated

RQ (Reportable Qty) 49 CFR 172.101 Not applicable

Section 15 Regulatory Information

US Federal Regulations TSCS (Toxic Substances Control Act) Status

Cercla RQ-40CFR 302.4 (a) RQ (lbs)

Cercla RQ-40CFR 302.4 (b) Materials without a "listed" RQ may be reportable as an "unlisted hazardous substance. See CFR 302.5 (b)

Sara 302 Components- 40 CFR 355 Appendix A
NONE

Section 311/312 Hazard Class—40 CFR 370.2

Immediate () Delayed () Fire () Reactive () Sudden Release of Pressure ()

Sara 313 Components—40 CFR 372.65 Section 313 Component(s)
None

International Regulations inventory status: Not Determined

State and Local Regulations CALIFORNIA PROPOSITION 65
None

New Jersey RTK Label Information:
None

Pennsylvania RTK label information
None

Section 16 Other Information

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is, current, applicable, and suitable to their circumstances. No representation or warranties, either expressed or implied of fitness for a particular purpose or of any other nature to the product or to the information herein is made hereunder. Angelus shall in no event be responsible for any damages of whatsoever nature directly or indirectly resulting from the publication, or use of, or reliance upon the information contained herein.

#AEC

Angelus Shoe Polish Inc.

PRODUCT: Angelus #840 Easy Cleaner
PREPARED: 09/01/06

MATERIAL SAFETY DATA SHEET

EMERGENCY PHONE NUMBERS (562) 229-0521

Page 1 of 4

SECTION I PRODUCT IDENTIFICATION *

*****PROD

UCT NAME: Angelus Easy Cleaner

CHEMICAL FAMILY: A proprietary water-based surfactant product.

MIS HAZARD RATING:

Health	1	4=Extreme
Fire	0	3=High
Reactivity	0	2=Moderate
		1=Slight
		0=Insignificant

SECTION II HAZARDOUS MATERIALS *

*****Sodiu

m Dodecylbenzene Sulfonate

1%

CAS. NO. 25155-30-0

TLV ppm NA, mg/cubic meter NA

See Section V.

SECTION III PHYSICAL DATA *

*****APPE

ARANCE & ODOR:	Clear liquid; soap-like odor.
SOLUBILITY IN WATER:	complete
DENSITY:	1 g/l Approx.
SPECIFIC GRAVITY:	1 Approx.
BOILING POINT:	not measured
pH:	not measured
DECOMPOSITION TEMP:	not measured
FREEZING POINT:	not measured
MELTING POINT:	not measured
% VOLATILE:	25% by weight
EVAPORATION RATE:	not measured
VAPOR DENSITY:	not measured
VAPOR PRESSURE:	not measured
IGNITION TEMPERATURE:	not measured
VISCOSITY:	not measured

Page 2 of 4

SECTION IV FIRE AND EXPLOSION DATA *

*****FLAS

H POINT:	nonflammable
EXPLOSIVE LIMIT:	not measured
EXTINGUISHING MEDIA:	Carbon dioxide, water spray, foam or dry chemical

SPECIAL PROCEDURES: Use self-contained breathing apparatus and full protective clothing.

USUAL HAZARDS: none

As the product is water-based, combustion should not take place.

SECTION V HEALTH INFORMATION *

(ADVERSE HEALTH EFFECTS THAT MAY OCCUR FROM OVEREXPOSURE)

This product contains Sodium Dodecylbenzene Sulfonate, CAS No. 25155-30-0

SECTION VI OCCUPATIONAL EXPOSURE LIMITS *

THRESHOLD LIMIT- NONE

SECTION VII EMERGENCY AND FIRST AID PROCEDURE *

INHALATION:

NONE. MIST SHOULD BE CONSIDERED A NUISANCE PARTICULATE.

EYE CONTACT:

FLUSH THOROUGHLY WITH WATER FOR 15 MINUTES.

CONSULT PHYSICIAN IF IRRITATION CONTINUES.

SKIN CONTACT:

NO ADVERSE REACTION EXPECTED. IF IRRITATION DEVELOPS FLUSH WITH WATER.

INGESTION:

CONSULT A PHYSICIAN IF NECESSARY

ADDITIONAL MEASURES:

NONE FOUND

SECTION VIII REACTIVITY DATA *

*****CHE

MICAL STABILITY: STABLE

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

-----CONDITIONS TO AVOID:

NONE FOUND

-----HAZARDOUS

DECOMPOSITION PRODUCTS:

NONE

SECTION IX SPILL OR LEAK PROCEDURES *

SPILL OR LEAK PROCEDURES:

COLLECT ONTO INERT ABSORBANT. PLACE IN SUITABLE CONTAINER. RINSE RESIDUAL WITH WATER. SMALL SPILLS MAY BE FLUSHED TO AN INDUSTRIAL WASTE DISPOSAL: SMALL QUANTITIES MAY BE FLUSHED IN AN INDUSTRIAL SEWER. LARGE AMOUNTS SHOULD BE DISPOSED OF OR INCINERATED IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS.

SECTION X EMPLOYEES PROTECTION *

*****RESPI

RATORY PROTECTION:

NONE REQUIRED. NORMAL VENTILATION SHOULD BE ADEQUATE.

-----PROTECTIVE CLOTHING:

NONE NECESSARY. INDIVIDUALS WITH SENSITIVE SKIN SHOULD WEAR LATEX GLOVES. SAFETY GLASSES MAY BE WORN.

-----ADDITIONAL MEASURES:

NORMAL VENTILATION ADEQUATE.

SECTION XI SPECIAL PRECAUTIONS *

*****NONE

SECTION XII TRANSPORTATION AND OTHER REGULATORY *

* REQUIREMENTS *

DOT PROPER SHIPPING NAME: Liquid Soap

DOT CLASSIFICATION: none, not regulated

OTHER: none found

TSCA: All ingredients listed

SARA TITLE III: none

CALIFORNIA PROP. 65: none detectable

This document was designed to, and to the best of our knowledge conforms with OSHA Hazard Communication Standard 29CFR 1910-1200.

#ALD

Angelus Shoe Polish Co.
Santa Fe Springs, Ca. 90670

Product: Angelus No. 500 Leather Dye
Date Prepared: 08/15/09

Section 1 Product Identification
Product: Angelus Leather Dye / Neutral & various colors
General or Generic ID: Alcohol / Glycol Ether solvent blend

Hazard Rating: Health 2 Scale: 0 Minimal 1 Slight 2 Moderate 3 Serious 4 Severe
Fire 3
Reactivity 0

Emergency Phone Number 562-229-0521

Emergency Phone for Transportation only: 1-800-535-5053 INFOTRAC

Section 2 Composition/Information of Ingredients

Ingredient (s)	CAS Number	% (by volume)
Ethanol	64-17-5	>40
1-Methoxy-2-Propanol	107-98-2	>8
Methanol	67-56-1	<4
2-Propanol	67-63-0	1

Section 3 Hazards Identification Potential Health Effects

Eye: Can cause eye irritation. Symptoms include stinging, tearing, redness, and swelling of eyes.

Skin: Exposure may cause mild skin irritation. Symptoms may include redness and burning. Skin absorption is possible, and may contribute to symptoms of toxicity from other routes of exposure.

Swallowing/Ingestion: Small single dose oral toxicity is low and is not likely to cause harmful effects: swallowing large amounts may be harmful. Ingestion of moderate quantities of methanol also produces acidosis.

Inhalation: Exposure to vapor or mist is possible. Short-term inhalation toxicity is low. Breathing small amounts during normal handling is not likely to cause harmful effects; breathing large amounts may be harmful. Always use proper ventilation.

Symptoms of Exposure: Gastrointestinal irritation (nausea, vomiting, diarrhea), irritation (nose,throat, respiratory tract), vomiting, headache, dizziness, shortness of breath, drunken behavior, visual disturbance, fatigue, unconsciousness , complete blindness, and death.

Cancer Information: No Data

Other Health Effects: No Data

Primary Route (s) of Entry: Inhalation, skin absorption, skin contact.

Page One

Continued on next page

Section 4	First Aid Measures:
Eye Contact:	Flush eyes with water for 15 minutes while holding eyelids apart. Seek medical attention.
Skin Contact:	Remove contaminated clothing. Wash skin with soap and water. If symptoms persist seek medical attention. Launder clothing before reuse.
Swallowing/Ingestion:	If swallowed , seek medical attention. If individual is drowsy or unconscious do not give anything by mouth; place individual on the left side with the head down. If individual is conscious and alert, induce vomiting by giving syrup of ipecac or by gently placing two fingers at the back of the throat. If possible, do not leave individual unattended. It is best if possible to seek medical advise before the inducement of vomiting.
Inhalation:	Remove to fresh air. Give artificial respiration if not breathing. If breathing is difficult, oxygen may be given by qualified personnel. Obtain medical attention.
Note to Physicians:	The major toxicity of this material will arise from its methyl alcohol content. Treatment should include the following: Hemodialysis, the intravenous administration of ethanol (10ml per hour) to interfere with the metabolism of methyl alcohol; and the administration of sodium bicarbonate to correct acidosis.

Section 5	Fire Fighting Measures:
Flash Point:	64F
Explosive Limit:	No Data
Autoignition Temp:	No Data
Hazardous Products of Combustion:	carbon dioxide and carbon monoxide, various hydrocarbons.
Fire/Explosion Haz:	Never use welding or cutting torch on or near container (even empty) because product (even slight residue) can ignite explosively. Vapors may travel or be moved by air currents and ignited by pilot lights, other flames, smoking, sparks, static discharges or other ignition sources at locations distant from product handling point. Vapors may settle in low or confined areas or travel a long distance to an ignition source and flash back explosively. Static ignition hazard can result for handling and use. Electrically bond and ground all containers and equipment. This material may produce a floating fire hazard. Flame may be invisible. Approach fire with caution.
Extinguishing Media:	regular foam, water fog, carbon dioxide, dry chemical., alcohol foam.
Fire Fighting Instructions:	Use NIOSH-approved self-contained breathing apparatus and complete protective clothing when fighting chemical fires. Cool fire-exposed containers with water spray. NFPA rating: Not determined.

 Section 6 Accidental Release Measures

Small Spills: Contain spill and ventilate area. Absorb on inert media and containerize for disposal.

Large Spills: Eliminate all ignition sources (flares, flames including pilot lights, electrical sparks). Persons not wearing protective equipment should leave area until cleanup is completed. Stop spill at source. Prevent from entering drains, sewers, or any other bodies of water. Prevent from spreading. If runoff occurs, notify authorities as required. Dispose of in accordance with all regulations.

Additional information: It is always best to wear complete protective clothing when cleaning up chemical spills. Spills and releases may have to be reported to federal and / or local authorities.

Section 7 Handling and Storage

Handling: Containers of this material may be hazardous when emptied. All containers larger than one gallon should be grounded and/or bonded when material is transferred. Any use of this product in elevated temperature process should be thoroughly evaluated to establish and maintain safe operating conditions. Always use adequate ventilation.

Storage: Keep container closed when not in use. Keep away from heat, sparks and open flames. Do not store this material above 49C (120 F). The empty container is hazardous.

Section 8 Exposure Controls / Personal Protection

Eye Protection: Wear chemical safety goggles in compliance with OSHA regulations.

Skin Protection: Wear impervious gloves and impervious clothing and boots.

Respiratory Protection: If engineering controls do not maintain airborne concentrations below recommended limits, use a NIOSH-approved respirator for organic vapors. (consult your industrial hygienist).

Engineering Controls: Provide sufficient ventilation to maintain exposure below TLV (s)

Exposure Guidelines:	OSHA VPEL	ACGIH TLV
Ethanol cas 64-17-5		1000 ppm
Isopropanol cas 67-63-0		400 ppm
Methanol cas 67-56-1		200 ppm
1-Methoxy-2-Propanol cas 107-98-2	100 ppm TWA 150 ppm STEL	100 ppm TWA 150 ppm STEL

Angelus Shoe Polish

No. 500 Leather Dye Page 4

08/15/09

 Section 9 Physical and Chemical Properties VOC 741 gr/l

Boiling Point: No Data

Vapor Pressure No Data

Specific Vapor Density: No Data

Specific Gravity: No Data

Liquid Density: 7.5 lbs. per gallon @ 77F

Percent Volatiles: >85

Evaporation Rate: (Butyl Acetate =1) 3

Appearance / State: Appearance: Clear transparent to deep color State: Liquid

odor: slight / sweet / alcohol odor

 Section 10 Stability and Reactivity

Hazardous Polymerization: Hazardous Polymerization will not occur.

Hazardous Decomposition: May form: carbon dioxide and carbon monoxide, various hydrocarbons.

Conditions to Avoid: Keep away from heat, sparks, and open flames., strong oxidizing agents.

Chemical Stability: Stable.

Incompatibility: Avoid strong oxidizing agents.

 Section 11 Toxicological Information: NO DATA

 Section 12 Ecological Information: NO DATA

 Section 13 Disposal Considerations

 Waste Management: Dispose of all materials in accordance with all applicable local, state and federal regulations.

 Section 14 Transportation Information

Shipping Marks: Flammable Liquid N.O.S. (ethyl alcohol) hazard class 3 UN1993 PG group II item 58420 class 55

Additional: Refer to DOT 49 CFR 172.101

Page 04 Continued on next page

Section 15 Regulatory Information

US Federal Regs: TSCA (Toxic Substances Control Act) Status
 TSCA (United States) The intentional ingredients of this product are listed.

CERCLA RQ-40CFR 302.4 (a) RQ (lbs)
 Component: None

CERCLA RQ-40-CFR 302.4 (b) Materials without a “Listed” RQ may be reportable as an “unlisted hazardous substance”. See 40 CFR 302.5 (b)

SARA 302 Components-40 CFR 355 appendix A TPQ lbs RQ (lbs) Section 3
 component (s) None

Section 311/312 Hazard Class-40 CFR 270.2

Immediate (X) Delayed (X) Fire (X) Reactive () sudden release of pressure ()

SARA 313 Components 40 CFR 372.65 Section 313 Component (s) CAS NO %
 Methanol 67-56-1 <4

State and Local Regulations : CALIFORNIA PROPOSITION 65

The following statement is made in order to comply with the California Safe Drinking Water and Toxic Enforcement Act of 1986: This product contains the following substance (s) know to the State of California to cause cancer. None

The following statement is made in order to comply with the California Safe Drinking Water and Toxic Enforcement Act of 1986: This product contains the following substance know to the state of California to cause reproductive harm . None

Additional RTK info: The following chemicals are on the following RTK:

New Jersey RTK label information Propylene Glycol Monomethyl Ether Cas 107-98-2

Pennsylvania RTK Label Information 2-Propanol, 1-Methoxy- Cas 107-98-2

The information herein is presented in good faith and is believed to be correct as of the date hereof. However Angelus Shoe Polish makes no representation as to the completeness and accuracy thereof. Users must make their own determination as to the suitability of the product for their purposes prior to use. No representation or warranties, either expressed or implied of fitness for a particular purpose or of any other nature to the product or to the information herein is made hereunder. Angelus shall in no event be responsible for any damages of whatsoever nature directly or indirectly resulting from the publication, or use of, or reliance upon the information contained herein.

#ALP

Angelus Shoe Polish Co.
Santa Fe Springs, Ca. 90670

Product: Angelus No. 720 Acrylic Leather Paint
Date Prepared: 06/05/07

Section 1 Product Identification
Product Name: Angelus Acrylic Leather Paint / Neutral and 60+ colors
General or Generic ID: A proprietary resin emulsion product

Hazard Rating: Health 1 Scale: 0 Minimal 1 Slight 2 Moderate 3 Serious 4 Severe
Fire 0
Reactivity 0

Emergency Phone Number 562-229-0521 Emergency Phone for Transportation only: 1-800-535-5053 INFOTRAC

Section 2 Composition/Information of Ingredients

Ingredient (s)	CAS Number	% (by volume)
Blend of Acrylic Polymers and Copolymers		<10
Various Colorants when necessary		<9

Section 3 Hazards Identification Potential Health Effects

Eye: Can cause eye irritation. Symptoms include stinging, tearing, redness, and swelling of eyes.

Skin: May cause irritation of skin with prolonged use. No problem is expected with normal use.

Swallowing/Ingestion: May cause nausea. Vomiting may be induced at the discretion of a physician.

Inhalation: None, No adverse effect expected with normal use and adequate ventilation.

Symptoms of Exposure: None. No adverse effect expect with normal use..

Target Organ Effects: Not Determined

Developmental Info: Not Determined

Cancer Information: Based on the available information, this material cannot be classified with regard to carcinogenicity.

Primary Route of entry: Inhalation, Skin contact, Eye contact, Ingestion.

Other Health Effects: No Data

Section 4 First Aid Measures

Eyes: Flush eyes gently with water for at least 15 minutes .Seek medical attention if irritation persists.

Skin: Wash affected skin areas thoroughly with soap and water. Consult physician if irritation persists.

Swallowing/Ingestion: If swallowed give 2 glasses of water. Consult a physician. Never give anything by mouth to an unconscious person.

Inhalation: Move subject to fresh air. If symptoms persist consult a physician.

Page One Continued on next page

Angelus Shoe Polish

No. 720 Acrylic Leather Paint

Page 2

06/05/07

Section 5 Fire Fighting Measures

Flash Point: Noncombustible

Explosive Limit: Not Applicable

Autoignition Temp: Not Applicable

Hazardous products from Combustion: Not measured

Fire & Explosion Haz: Material may splatter above 212F/100C. Polymer film can burn.

Extinguishing Media: Use extinguishing media appropriate for surrounding fire.

Fire Fighting Instructions: Wear a self-contained breathing apparatus with a full face piece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protection equipment.

NFPA Rating: Health—1, Flammability---0, Reactivity--0

Section 6 Accidental Release Measures

Spill: Absorb liquid on vermiculite, floor absorbent, or other absorbent material and place in an approved container. Follow all regulations concerning disposal.

Section 7 Handling and Storage

Handling: Keep product from freezing..

Section 8 Exposure Controls / Personal Protection

Eye Protection: Under normal conditions eye protection is not necessary. It is however good practice to always wear protective glasses when using any product.

Skin Protection: Under normal conditions protections is not necessary. It is good practice to always avoid contact with skin.

Respiratory Protection: With normal ventilation respiratory protection is not necessary.

Exposure Guidelines: OSHA VPEL ACGIH TLV
Non Hazardous

Section 9 Physical and Chemical Properties

Boiling Point: 212F / 100C

Vapor Pressure Not measured

Specific Vapor Density: AIR=1 <1 water

Page 2

Continued on next page

Angelus Shoe Polish

No. 720 Acrylic Leather Paint

Page 3

06/05/07

Section 9 continued Physical and Chemical Properties

Percent Volatiles: None

Volatile Organic Compounds (VOC) 7% by weight / .56 lbs. / gallon

Evaporation Rate: Slower than Ethyl Ether

Appearance: Clear /Milky liquid and various colors

State: Liquid

Physical Form: Homogeneous Solution

Color: No Data

Odor: minimal

pH N/A

Section 10 Stability and Reactivity

Hazardous Polymerization: Product will not undergo hazardous polymerization.

Hazardous Decomposition: Thermal decomposition may yield acrylic monomers.

Chemical Stability: Stable

Incompatibility: There are no known materials which are incompatible with this product.

Section 11 Toxicological Information
No Data

Section 12 Ecological Information: No Data

Section 13 Disposal Consideration

Waste Management: Dispose of in accordance with all applicable local, state and federal regulations.

Section 14 Transport Information 49 CFR 172.101

Dot Description: Not Regulated

RQ (Reportable Qty) 49 CFR 172.101 Not applicable

Section 15 Regulatory Information

US Federal Regulations TSCS (Toxic Substances Control Act) Status

Cercla RQ-40CFR 302.4 (a) RQ (lbs)

Cercla RQ-40CFR 302.4 (b) Materials without a "listed" RQ may be reportable as an "unlisted hazardous substance. See CFR 302.5 (b)

Sara 302 Components- 40 CFR 355 Appendix A
NONE

Section 311/312 Hazard Class—40 CFR 370.2

Immediate () Delayed () Fire () Reactive () Sudden Release of Pressure ()

Sara 313 Components—40 CFR 372.65 Section 313 Component(s)
None

International Regulations inventory status: Not Determined

State and Local Regulations CALIFORNIA PROPOSITION 65
None

New Jersey RTK Label Information:
None

Pennsylvania RTK label information
None

Section 16 Other Information

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is, current, applicable, and suitable to their circumstances. No representation or warranties, either expressed or implied of fitness for a particular purpose or of any other nature to the product or to the information herein is made hereunder. Angelus shall in no event be responsible for any damages of whatsoever nature directly or indirectly resulting from the publication, or use of, or reliance upon the information contained herein.

#ALPD

Angelus Shoe Polish Co.
Santa Fe Springs, Ca. 90670

Product: Angelus No 820 Leather Preparer & Deglazer
Date Prepared: 04-02-07

Section 1 Product Identification
Product: Angelus Leather Preparer No. 820
General or Generic ID: Acetone / Solvent Blend

Hazard Rating: Health 1 Scale: 0 Minimal 1 Slight 2 Moderate 3 Serious 4 Severe
Fire 3
Reactivity 0

Emergency Phone Number 1-562-229-0521

Emergency Phone for Transportation only: 1-800-535-5053 INFOTRAC

Section 2 Composition/Information of Ingredients

Hazardous Ingredients

Ingredient (s)	CAS Number	% (by volume)
Solvent Naphtha (Petroleum), Medium Aliphatic	64742-88-7	<10
Acetone	67-64-1	>70

Section 3 Hazards Identification Potential Health Effects

Eye: One or more components of this material is a severe eye irritant. Direct contact with the liquid or exposure vapors or mists may cause stinging, tearing, redness, swelling, and eye damage.

Skin: One or more components of this material is a skin irritant. Direct contact with this material may cause redness and burning, drying and cracking of the skin and skin damage.

Skin Absorption: Contact may result in skin absorption but symptoms of toxicity are not anticipated by this route alone under normal conditions of use. Persons with pre-existing skin disorders may be more susceptible to the effects of this material.

Swallowing/Ingestion: One or more components of this material is toxic and may be harmful if swallowed. Symptoms of toxicity may include: signs of nervous systems depression (eg: drowsiness, loss of coordination, and fatigue) Irritation of the digestive tract. Nausea, vomiting, and diarrhea. Material may enter lungs during swallowing or vomiting. This results in lung inflammation or other lung injury.

Inhalation: One or more components of this material is toxic by inhalation. Breathing vapors or mists may be harmful. Symptoms of toxicity may include: Irritation of the nose and throat. Signs of nervous systems depression (eg: drowsiness, dizziness, loss of coordination, fatigue), nausea, headaches, and vomiting. Respiratory symptoms associated with pre-existing lung disorders (eg: asthma-like conditions) may be aggravated by exposure to this material.

Section 4

First Aid Measures:

Eye Contact:	Immediately move victim away from exposure to vapors and into fresh air. If irritation or redness develops, flush eyes with clean water and seek immediate medical attention. For direct contact, hold eyelids apart and flush the affected eye(s) with clean water for at least 20 minutes. Seek immediate medical attention.
Skin Contact:	Remove contaminated clothing. Wash skin with soap and water. If symptoms persist seek medical attention. Launder clothing before reuse.
Swallowing/Ingestion:	If swallowed, seek medical attention. If individual is drowsy or unconscious do not give anything by mouth; place individual on the left side with the head down. If individual is conscious and alert, induce vomiting by giving syrup of ipecac or by gently placing two fingers at the back of the throat. If possible, do not leave individual unattended. It is best if possible to seek medical advice before the inducement of vomiting. SEEK MEDICAL ATTENTION
Inhalation:	Remove to fresh air. Give artificial respiration if not breathing. If breathing is difficult, oxygen may be given by qualified personnel. Obtain medical attention.
Note to Physicians:	Exposure to high concentrations of this material (eg: in enclosed spaces or with deliberate abuse) may be associated with cardiac arrhythmias. Epinephrine and other sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to this material. Other drugs with less arrhythmogenic potential should be considered. If sympathomimetic drugs administered, observe for the development of cardiac arrhythmias.

Section 5

Fire Fighting Measures:

Flash Point:	0 F
Explosive Limit:	No Data
Auto ignition Temp:	No Data
Hazardous Products of Combustion:	carbon dioxide and carbon monoxide, various hydrocarbons.
Fire/Explosion Haz:	Never use welding or cutting torch on or near container (even empty) because product (even slight residue) can ignite explosively. Vapors may travel or be moved by air currents and ignited by pilot lights, other flames, smoking, sparks, static discharges or other ignition sources at locations distant from product handling point. Vapors may settle in low or confined areas or travel a long distance to an ignition source and flash back explosively. Static ignition hazard can result for handling and use. Electrically bond and ground all containers and equipment. This material may produce a floating fire hazard. Flame may be invisible. Approach fire with caution.
Extinguishing Media:	regular foam, water fog, carbon dioxide, dry chemical., alcohol foam.
Fire Fighting Instructions:	Use NIOSH-approved self-contained breathing apparatus and complete protective clothing when fighting chemical fires. Cool fire-exposed containers with water spray. NFPA rating: Not determined.

Section 6 Accidental Release Measures

Small Spills: Contain spill and ventilate area. Absorb on inert media and containerize for disposal.

Large Spills: Eliminate all ignition sources (flares, flames including pilot lights, electrical sparks). Persons not wearing protective equipment should leave area until clean up is completed. Stop spill at source. Prevent from entering drains, sewers, or any other bodies of water. Prevent from spreading. If runoff occurs, notify authorities as required. Dispose of in accordance with all regulations.

Additional information: It is always best to wear complete protective clothing when cleaning up chemical spills. Spills and releases may have to be reported to federal and / or local authorities.

Section 7 Handling and Storage

Handling: Containers of this material may be hazardous when emptied. All containers larger than one gallon should be grounded and/or bonded when material is transferred. Any use of this product in elevated temperature process should be thoroughly evaluated to establish and maintain safe operating conditions. Always use adequate ventilation.

Storage: Keep container closed when not in use. Keep away from heat, sparks and open flames. Do not store this material above 49C (120 F). The empty container is hazardous.

Section 8 Exposure Controls / Personal Protection

Eye Protection: Wear chemical safety goggles in compliance with OSHA regulations.

Skin Protection: Wear impervious gloves and impervious clothing and boots.

Respiratory Protection: If engineering controls do not maintain airborne concentrations below recommended limits, use a NIOSH-approved respirator for organic vapors. (consult your industrial hygienist).

Engineering Controls: Provide sufficient ventilation to maintain exposure below TLV (s)

Exposure Guidelines:	OSHA PEL	OSHA VPEL	ACGIH TLV
Acetone 67-64-1	1000.000ppm	750.000ppm TWA 1000.000ppm STEL	500.000 ppm TWA 750.000 ppm STEL

Section 9 Physical and Chemical Properties

Boiling Point: No Data

Vapor Pressure No Data

Specific Vapor Density: No Data

Specific Gravity: No Data

Liquid Density: 6.53 lbs. per gallon @ 77F

Percent Volatiles: >30

Evaporation Rate: (Butyl Acetate =1) n/a

Appearance / State: Appearance: Clear transparent State: Liquid

odor: slight / mild / sweet

Section 10 Stability and Reactivity

Hazardous Polymerization: Hazardous Polymerization will not occur.

Hazardous Decomposition: May form: carbon dioxide and carbon monoxide, various hydrocarbons.

Conditions to Avoid: Keep away from heat, sparks, and open flames, strong oxidizing agents.

Chemical Stability: Stable.

Incompatibility: Avoid strong oxidizing agents.

Section 11 Toxicological Information: NO DATA

Section 12 Ecological Information: NO DATA

Section 13 Disposal ConsiderationsWaste Management: Dispose of all materials in accordance with all applicable local, state and federal regulations.

Section 14 Transportation Information

Shipping Marks: Paint Related Material UN 1263 Flammable Liquid

Additional: Refer to DOT 49 CFR 172.101

Page 04 Continued on next page

Section 15 Regulatory Information

US Federal Regs: TSCA (Toxic Substances Control Act) Status
 TSCA (United States) The intentional ingredients of this product are listed.

CERCLA RQ-40CFR 302.4 (a)	RQ (lbs)
Component: Acetone	5000

Section 302 component (s) 40 CFR 355 Appendix A
 none

Section 311/312 Hazard Class-40 CFR 270.2
 Immediate (X) Delayed () Fire (X) Reactive () sudden release of pressure ()

SARA 313 Components 40 CFR 372.65	Section 313 Component (s)	CAS NO	%
	None		

OSHA Process Safety Management 29 CFR 1910
 none listed

EPA Accidental Release Prevention 40 CFR 68
 none listed

State and Local Regulations : CALIFORNIA PROPOSITION 65

The following statement is made in order to comply with the California Safe Drinking Water and Toxic Enforcement Act of 1986: This product contains the following substance (s) know to the State of California to cause cancer. None Known

The following statement is made in order to comply with the California Safe Drinking Water and Toxic Enforcement Act of 1986: This product contains the following substance know to the state of California to cause reproductive harm. None

Additional RTK info: The following chemicals are on the following RTK:

New Jersey RTK label information	ACETONE	67-64-1
Pennsylvania RTK Label Information	2-PROPANONE	67-64-1

Section 16 Other Information

The information herein is presented in good faith and is believed to be correct as of the date hereof. However Angelus Shoe Polish makes no representation as to the completeness and accuracy thereof. Users must make their own determination as to the suitability of the product for their purposes prior to use. No representation or warranties, either expressed or implied of fitness for a particular purpose or of any other nature to the product or to the information herein is made hereunder. Angelus shall in no event be responsible for any damages of whatsoever nature directly or indirectly resulting from the publication, or use of, or reliance upon the information contained herein.

