

# PERMA TRANS™ Light Fabric Transfer



## Inkjet Transfer Paper for White and Light Colored Fabrics

Product Code: S421  
Double Red Line

### ITEMS YOU WILL NEED

- Prewashed white or light colored Cotton or Cotton/Polyester blend fabric or stretchable fabric like Lycra™
- Heat Press or Iron (do not use steam)
- Pillowcase
- Hard smooth surface (example: Formica, DO NOT USE AN IRONING BOARD)

### STEP ONE – PRINTING YOUR IMAGE

- 1) Bring paper to room temperature before printing.
- 2) Load transfer sheets into your printer so that the image is printed on the non-glossy (unlined) side.
- 3) Using your computer, select or design images to be transferred. **Mirror or flip the image before printing.**
- 4) Print image/design on paper using the following recommended print settings\*:

HP Media: Premium Matte Photo Paper  
Print Mode: Normal or Best

Epson Media: Plain Paper  
Print Mode: Photo

Canon Print Type: Standard  
Media: T-Shirt Transfer  
Print Mode: Standard

\*All technical information and recommendations are based on tests we have conducted. For inkjet printers not listed, we recommend following the manufacturer's instructions. Users should conduct their own tests before proceeding.

- 5) Use scissors to trim image/design from transfer sheet to remove excess area.

### STEP TWO – TRANSFERRING THE IMAGE

#### HEAT PRESS

- 1) Preheat press to 350°-375° F.
- 2) Press fabric for 3-5 seconds to release moisture and remove wrinkles.
- 3) Place printed image face down on the garment (the lined side will be facing up).
- 4) Set at medium pressure for best results.
- 5) Press for 25-30 seconds.
- 6) Peel immediately for best results (HOT Peel). Remove the backing paper from the transfer using a smooth, even motion while the transfer is still HOT.

### HAND IRON

- 1) Preheat your iron to the "Linen" setting. Lay a pillowcase on the ironing surface.
- 2) Pre-iron the fabric to release moisture and remove wrinkles.
- 3) Place your printed image face down on the garment (the lined side will be the ironing surface).
- 4) Using FIRM, STEADY pressure, glide the iron in a circular motion over the entire transfer for 2 minutes. It is important to cover the transfer completely.
- 5) After ironing each section of the transfer, glide the iron once more over the entire transfer to heat evenly.
- 6) Peel immediately for best results (HOT Peel). Remove the backing paper from the transfer using a smooth, even motion while the transfer is still HOT.

### WASHING INSTRUCTIONS

- Turn the garment inside out.
- Wash in COLD water.
- Use a mild detergent for best results.
- Do not use bleach or bleach alternative detergents.
- Remove the garment promptly from the washer. The color may bleed if left in the washer.
- Dry on LOW temperature.

### NOTES

- Test results demonstrate better color retention after washing using hot peel method.
- When transferring several images to the same fabric, wait until all images are transferred before peeling the backing paper to prevent the heat from affecting already transferred images.
- Store unused transfer papers in a resealable polybag in a flat, cool, dry area.

Check out our complete line of paper coating technologies:



Please be sure to evaluate the Standard Product Fact Sheet to ensure the product is compatible with your printer and ink. ALWAYS test to determine the suitability of this paper for use with your equipment and your methods. The Seller's and Manufacturer's maximum obligation shall be to replace any paper that has been proven to be defective. Neither the Seller nor the Manufacturer shall be liable for any injury, direct or consequential, arising out of the use of, or inability to use, this paper.

This product is protected under one or more of the following patents: 2012/0202,020/6,410,200/6,497,781/6,723,773/7,008,746/8,197,918/RE42,541

11 July 2018